



8140 Industrial Parkway, Suite 8 ♦ Sacramento, CA 95824
 Tel: (916) 383-6800 ♦ Fax: (916) 383-7794

<http://www.nttworldwide.com>
info@nttworldwide.com <http://www.dgaequipment.com>

GLASS SYRINGE – 100ML

Product Specifications



Catalog No.	Description
1005190	Glass Syringe – 100ml Interchangeable borosilicate glass syringe with permanently fused graduations and unique identifier. Reinforced flanges are flat on two sides to avoid rolling. Supplied with metal luer-lock tip.

Dimensions

Piston Outside Diameter	35.70 mm
Barrel Diameter Outside (D1)	41.16 mm
Barrel Collar Diameter (D2)	42.74 mm ± 0.05 mm
Piston Collar Diameter (D3)	55.12 mm ± 0.05 mm
Length (L)	214.50 mm ± 0.10 mm
Tolerance	0.0065 ± 0.0010 mm between plunger & barrel
Volume	100 ml (cc) ± 1.50 ml (cc)

Glass Properties

Expansion coefficient	52 ± 10 ⁻⁷ /centigrade
Density	2.36g ± 0.02g cm ³
Modulus of elasticity	64 ± 10 ³ mm ⁻²
Water resistance	First Class
Acid resistance	First Class
Alkali resistance	First Class
Softening point	785 °C
Melting temperature	1260 °C
Strain point	525 °C
Annealing point	570 °C
Hardness	7
Color	Clear

How to reach NTT

For routine requests for information, you can contact us via phone, mail, or e-mail through the internet at info@nttworldwide.com or through our website: <http://www.nttworldwide.com>

Business hours:	Pacific Standard Time	Monday through Friday 9:00 AM - 5:00 PM	
Phone:	916-383-6800	Shipping/Mailing	Northern Technology & Testing
Fax:	916-383-7794	Address:	8140 Industrial Parkway, #8
Toll Free:	800-590-0688		Sacramento, CA 95824